

Lift Tables - Horizontal Double Scissors Specifications, TLH 6000

Model	TLH 6000
Art. No.	614401
Capacity	6000 kg
Lift stroke	820 mm
Lowest height	250 mm
Length	2600 mm
Width	800 mm
Lifting time	39 sec
kW	1,5
Weight pack. incl.	560 kg



Lift Tables - Horizontal Double Scissors

The horizontal double scissor lift table by EdmoLift is the solution you need to handle goods that are both heavy and long. The lift platform is equipped with a combination of two pairs of EdmoLift scissors to obtain the desired lift range and length of the scissor lift table. The lift maneuvers of the two pairs of scissors are mechanically controlled to achieve a parallel lift operation.

EdmoLift's horizontal double scissor lift tables make it possible to handle bulky goods in a safe and effective way. With different variations and models we offer a wide spectrum of possibilities. The load capacity is between two and ten metric tons, the lift range varies between 820 mm and 2000 mm and the size of the lift table can be as large as 6200 x 1500 mm.

The scissor lift table can be delivered in many different colors designed specifically to suit the wishes of the customer, along with a large range of accessories and control alternatives. A number of models are available in a durable format that are especially suited to intensive operations. The functionality of the horizontal double scissor lift table can be increased by equipping it with various accessories, such as a mechanical stop and a foot control.

Product features

- Scissor lift table load capacity - max 10 000 kg.
- Lift table platform length from 2600 mm to 6200 mm as a standard model.
- Comprehensive program of accessories and possibilities for customizing the scissor lift tables.
- Complies with European safety standard EN 1570-1 - CE certified.
- 24 V DC control unit and operating device with deadman's switch.
- IP54 approved electrical system.
- Safety spacing between all moving parts of the lift table.
- Overload protection.
- Adjustable trap prevention safety trip bars on all four sides of the platform.
- The lift table is equipped with hose burst valves and mechanical locks for servicing and maintenance.
- Maintenance-free bearing surface.
- PLC control with possibility to program various functions is included for the standard model. PLC control enables customization for specific requirements.
- User manual in 20 different languages.